



Unmanaged 10/100Mbps Switch With Fast Ethernet Fiber Port

This compact switch is designed for SOHO and the small and medium business (SMB). It provides 7 auto-sensing 10/100Mbps twisted-pair Fast Ethernet ports, plus a 100Mbps Fast Ethernet fiber port for server connection on a longer distance, reliable fiber cable. With plug-and-play installation, this switch provides an easy and cost-effective way to enhance workgroup performance.

The switch supports IEEE 802.3x Flow Control to allow servers to directly connect to the switch for fast, reliable data transfer. At 200Mbps full duplex, the switch provides high-speed data pipes to your servers with minimum data transfer loss.

Key Features

- 7 10/100Mbps Nway Ethernet ports
- 1 100BASE-FX Fast Ethernet port
- Full/half duplex transfer mode for each port
- Wire speed reception and transmission
- Store-and-Forward switching method
- Integrated address Look-Up Engine, supports 8K absolute MAC addresses
- Supports 256K bytes RAM for data buffering
- Extensive front-panel diagnostic LEDs

Technical Specifications

Standards

- IEEE 802.3 10BASE-T Ethernet
- IEEE 802.3u 100BASE-TX Fast Ethernet
- ANSI/IEEE 802.3 NWay auto-negotiation

Protocol

CSMA/CD

Topology

Star

Number of LAN Ports

- 7 x 10/100Mbps Nway MDI-X RJ-45 Ports
- 1 x 100BASE-FX Multimode Fiber Port

Data Transfer Rates

- Ethernet:
 - 10Mbps (half duplex)
 - 20Mbps (full duplex)
- Fast Ethernet:
 - 100Mbps (half duplex)
 - 200Mbps (full duplex)

Network Cables

- 10BASE-T:
 - 2-pair UTP Cat. 3, 4, 5 (100 m)
 - EIA/TIA-586 100-ohm STP (100 m)
- 100BASE-TX:
 - 2-pair UTP Cat. 5 (100m.)
 - EIA/TIA-568 100-ohm STP (100m max.)
- 100BASE-FX:
 - 62.5/125µm multimode fiber

Performance

Transmission Method

Store-and-forward

MAC Address Learning

Automatic update

Packet Filtering/Forwarding Rates

- Ethernet: 14,880 pps per port
- Fast Ethernet: 148,810 pps per port

RAM Buffer

256K Bytes per device

Office LAN

Physical & Environmental

Power Consumption

12 watts max.

DC Inputs

- 5VDC/2.4A

Operating Temperature

0° ~ 50° C

Storage Temperature

- 10° ~ 70° C

Humidity

10% ~ 90% non-condensing

Storage Humidity

5% ~ 90% non-condensing

Dimensions

171 x 98 x 29 mm (W x H x D)

Emission

- VCCI-B
- FCC Class B
- CE Mark B

Ordering Information

10/100Mbps Unmanaged Stand-alone Switch

DES-1008F 7 RJ-45 10BASE-T/100BASE-TX ports
1 SC 100BASE-FX Fast Ethernet fiber port

please specify one of the following after the model number:

- /A Includes an American standard AC power adapter
- /B Includes a U.K. standard AC power adapter
- /E Includes a German standard AC power adapter
- /N Includes an Australian standard AC power adapter
- /CN Includes a Chinese standard AC power adapter
- /U Includes no AC power adapter

D-Link®



Rev.01 (Dec. 2001)
Printed in Taiwan

U.S.A	TEL: 1-949-788-0805	FAX: 1-949-753-7033	www.dlink.com
Canada	TEL: 1-905-829-5033	FAX: 1-905-829-5095	www.dlink.ca
Europe	TEL: 44-20-8731-5555	FAX: 44-20-8235-5511	www.dlink.co.uk
U.K	TEL: 44-20-8731-5555	FAX: 44-20-8235-5511	www.dlink.co.uk
Germany	TEL: 49-61-96779900	FAX: 49-61-967799300	www.dlink.de
France	TEL: 33-1-30-23-86-88	FAX: 33-1-30-23-86-89	www.dlink.france.fr
Benelux	TEL: 31-40-2668713	FAX: 31-40-2668666	www.dlink-benelux.nl
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723	www.dlink.it
Iberia	TEL: 34-93-4090770	FAX: 34-93-4910795	www.dlinkiberia.es
Sweden	TEL: 46-(0)8-564-61900	FAX: 46-(0)8-564-61901	www.dlink.se
Norway	TEL: 47-22-991890	FAX: 47-22-207039	
Denmark	TEL: 45-43-96-90-40	FAX: 45-43-42-43-47	www.dlink.dk
Finland	TEL: 358-9-622-91660	FAX: 358-9-622-91661	www.dlink.fi.com
Singapore	TEL: 65-774-6233	FAX: 65-774-6322	www.dlink-intl.com
Australia	TEL: 61-2-9417-7100	FAX: 61-2-9417-1077	www.dlink.com.au
Japan	TEL: 81-3-5434-9678	FAX: 81-3-5434-9868	www.dlink.co.jp
China	TEL: 86-10-88097777	FAX: 86-10-88096789	
India	TEL: 91-22-652-6696	FAX: 91-22-652-8914	www.dlink-india.com
Middle East	TEL: 20-2-6356176	FAX: 20-2-6356192	www.dlink-me.com
South America	TEL: 56-2-232-3185	FAX: 56-2-232-0923	www.dlink.cl
South Africa	TEL: 27(0)126652165	FAX: 27(0)126652186	www.dlink.co.za
Russia	TEL: 7-095-737-3389	FAX: 7-095-737-3390	www.dlink.ru
Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515	www.dlinktw.com.tw
D-Link Corp.	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299	www.dlink.com.tw