

**Product Datasheet**

P/N D9000  
 Page 1 of 2  
 Rev. 4/2003-03-10

**Belden 1885 ENH**

**1000MHz Cat 7 ISTD FRNC**



**Application**

- Horizontal and building backbone cable.
- Support current and future **Category 7** applications, such as:  
 100 Base TX, 100 Base VG AnyLan, 155 ATM and 1000 Base-T (**Gigabit Ethernet**), FDDI.

**Key features and Standards**

- General standards: **ISO/IEC 11801 2<sup>nd</sup> edition (2002)**, **EN 50173 2<sup>nd</sup> edition (2001)**
- Provides extended performance far in excess of industry standards
- Superior NEXT performance

**Construction & Dimensions**



- Construction: 4 individually shielded twisted pairs
- Conductor: solid bare copper
- Conductor diameter: AWG 23 (0,60 mm)
- Conductor insulation material: Foam skin Polyolefine
- Diameter over insulation: 1.45 mm
- Shield: Tinned copper braid  
Coverage > 40%
- Ripcord: Polyester
- Jacket material: FRNC
- Outer diameter: 8,0 mm ± 0.30 mm

Pair 1	White/Blue
Pair 2	White/Orange
Pair 3	White/Green
Pair 4	White/Brown

**Electrical characteristics (at 20 °C)**

Nominal mutual capacitance at 1 kHz	48 nF/km
Maximum conductor DCR	75 Ohm/km
NVP - Nominal Velocity of Propagation	0.75 c
SKEW – Propagation delay difference (100 MHz)	typical ≤ 15 ns/100m
Mean Characteristic Impedance 4-1000 MHz <sup>1)</sup>	100 ± 5 Ohm

<sup>1)</sup> According to cable requirements of ISO/IEC 11801 category 7, Sept. 2002

**General and environmental characteristics**

Temperature range - operation	-20°C - +60°C
Temperature range - installation	+0°C - +50°C
Minimum bending radius - operation	30 mm
Minimum bending radius - installation	60 mm
Maximum pulling tension	90 N
Flame retardancy	IEC 60332-1
Caloric value	500 kJ/m
Weight (approx.)	60 kg/km
Maximum operating voltage	72 V rms
Maximum continuous current per conductor (25°C)	1.4 A

**Product Datasheet**

P/N D9000

Page 2 of 2

Rev. 4/2003-03-10

**Belden 1885 ENH**

**1000MHz Cat 7 ISTP FRNC**



**Electrical characteristics (at 20 °C)**

**Attenuation**

Frequency	1	4	10	16	20	31.2	62.5	100	155	250	600	1000	MHz
Spec. (Max.) <sup>1)</sup>	-	3.7	5.9	7.4	8.3	10.4	14.9	19.0	24.0	31.0	50.1	66.9	dB/100m
Typical	[1.9]	3.5	5.4	6.9	7.6	9.6	13.6	17.4	21.7	28.0	43.5	56.6	dB/100m

**NEXT (Near end crosstalk)**

Frequency	1	4	10	16	20	31.2	62.5	100	155	250	600	1000	MHz
Spec. (Min.) <sup>1)</sup>	-	80.0	80.0	80.0	80.0	80.0	75.5	72.4	69.5	66.4	60.7	57.4	dB/100m
Typical	[100]	100	100	100	100	100	100	95	95	95	90	90	dB/100m

**Power sum NEXT**

Frequency	1	4	10	16	20	31.2	62.5	100	155	250	600	1000	MHz
Spec. (Min.) <sup>1)</sup>	-	77.0	77.0	77.0	77.0	77.0	72.5	69.4	66.5	63.4	57.7	54.4	dB/100m
Typical	[98]	98	98	98	98	98	98	93	93	93	88	88	dB/100m

**Power sum ELFEXT**

Frequency	1	4	10	16	20	31.2	62.5	100	155	250	600	1000	MHz
Spec. (Min.) <sup>1)</sup>	-	75.0	71.0	66.9	65.0	61.1	55.1	51.0	47.2	43.0	35.4	31.0	dB/100m
Typical	[95]	95	95	90	87	84	80	76	72	67	60	56	dB/100m

**Power sum ACR**

Frequency	1	4	10	16	20	31.2	62.5	100	155	250	600	1000	MHz
Spec. (Min.) <sup>1)</sup>	-	73.3	71.1	69.6	68.7	66.6	57.6	50.4	42.6	32.5	7.6	-	dB/100m
Typical	[96]	94	92	91	90	88	84	75	71	68	44	31	dB/100m

**Return Loss**

Frequency	1	4	10	16	20	31.2	62.5	100	155	250	600	1000	MHz
Spec. (Min.) <sup>1)</sup>	-	23	25	25	25	23.7	21.5	20.1	18.8	17.3	17.3	13.1	dB/100m
Typical	[26]	30	35	35	35	34	32	31	29	29	28	20	dB/100m

<sup>1)</sup>: Specification values according to cable requirements of ISO/IEC 11801 category 7, Sept. 2002. Specification values at 1000 MHz are based on extrapolation of limits of mentioned standard.

Note: Values between brackets are for information only

**Ordering information**

**MARKING**

Text on the cable jacket                      Inkjet printing

**BELDEN 1885ENH ISTP CAT7 4PR AWG23 LSNH ISO/IEC 11801 EN50173  
(DIN 44312-5) -- TESTED TO 1000 MHZ -- VERIFIED 100 OHM**

Meter marking:                                      Yes

**JACKET COLOUR**

Colour	RAL code
Grey	RAL 7032

**PACKAGING (PUT UP)**

500m and 1000m Crate Reels